WeatherBond

ASAP® Insulation Fasteners



Overview

WeatherBond's pre-assembled ASAP (Assembled Screw And Plate) Insulation Fasteners consist of a standard #12 Insulation insulation fastener with a 3" round metal insulation plate or plastic locking insulation plate. ASAP Insulation Fasteners are used to attach insulation to wood (minimum ¹⁵/₃₂" [12 mm] CDX plywood) or steel decks (22-gauge [0.76 mm] or heavier). ASAP fasteners boost productivity by greatly reducing installation time when compared to loose fasteners and plates.

Features and Benefits

- Drill point designed for maximum installation efficiency
- Fasteners' coating provides excellent corrosion resistance, surpassing the FM 4470 requirements of less than 15% red rust after 15 cycles in the Kesternich cabinet
- One Phillips driver bit is provided in each box of fasteners

Installation

Place the ASAP fastener and plate at the desired location and install with a standard clutch drive electric screw gun. No pre-drilling is necessary for wood and steel (18 gauge or less) decks since the fastener is self-drilling. The minimum penetration depth (measured from the top surface) is 1" (25 mm) for wood and ¾" (19 mm) for steel.

REVIEW CURRENT WEATHERBOND INSTALLATION INSTRUCTIONS FOR SPECIFIC INSTALL ATION REQUIREMENTS.

Precautions

- 1. Eye protection is recommended during installation.
- 2. Use care to avoid over-driving the fastener.

Typical Properties and Characteristics

Size	Thread Length in (mm)	Weight (lbs/carton)	Packaging Fasteners/Carton
1 5%"	Full	12	250
2 1/4"	Full	16	250

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

