# SAFETY DATA SHEET

X-Tenda Coat XTRA Fiber Grade Mastic



# **Section 1. Identification**

GHS product identifier : X-Tenda Coat XTRA Fiber Grade Mastic

Product code : 358298
Other means of : Not available.

identification

Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

Sealants

Uses advised against

Not applicable.

Supplier's details : Weatherbond

P.O. Box 215 Plainfield PA 17081 USA

+1-866-471-5125

**Emergency telephone** number (with hours of

operation)

: +1-800-424-9300 (Chemtrec)

# Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the : SKIN IRRITATION - Category 2 substance or mixture : SKIN IRRITATION - Category 2A

**GHS label elements** 

Hazard pictograms :



Signal word : Warning

**Hazard statements** : H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

**Precautionary statements** 

**Prevention**: P280 - Wear protective gloves. Wear eye or face protection.

P264 - Wash thoroughly after handling.

**Response** : P362 + P364 - Take off contaminated clothing and wash it before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P332 + P313 - If skin irritation occurs: Get medical advice or attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage : Not applicable.

Disposal : Not applicable.

Hazards not otherwise

classified

: Releases small quantites of 2-butanone oxime and methanol during polymerization.

Date of issue/Date of revision : 11/9/2023 Date of previous issue : No previous validation Version : 1 1/11

# Section 3. Composition/information on ingredients

Substance/mixture
Other means of
identification

: Mixture

: Not available.

| Ingredient name                                | %       | CAS number  |
|--|---------|-------------|
| Nepheline syenite                              | 15 - 40 | 37244-96-5  |
| Poly[oxy(dimethylsilylene)]                    | 10 - 30 | 9016-00-6   |
| butan-2-one O,O',O"-(methylsilylidyne)trioxime | 3 - 7   | 22984-54-9  |
| Silica, amorphous, fumed, crystfree            | 1 - 5   | 112945-52-5 |
| titanium dioxide                               | 1 - 5   | 13463-67-7  |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

# Description of necessary first aid measures

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

# Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation.

**Ingestion**: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Date of issue/Date of revision : 11/9/2023 Date of previous issue : No previous validation Version : 1 2/11

# Section 4. First aid measures

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

# Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

: In a fire or if heated, a pressure increase will occur and the container may burst.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

# Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Date of issue/Date of revision : 11/9/2023 Date of previous issue : No previous validation Version : 1 3/11

# Section 6. Accidental release measures

# Methods and materials for containment and cleaning up

#### **Small spill**

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### **Precautions for safe handling**

### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

| Ingredient name  | Exposure limits   |  |
|------------------|---|--|
| titanium dioxide | OSHA PEL (United States, 5/2018).  TWA: 15 mg/m³ 8 hours. Form: Total dust OSHA PEL 1989 (United States, 3/1989).  TWA: 10 mg/m³ 8 hours. Form: Total dust CAL OSHA PEL (United States, 5/2018).  TWA: 5 mg/m³, (as Ti) 8 hours. Form: respirable fraction  TWA: 10 mg/m³, (as Ti) 8 hours. Form: total dust ACGIH TLV (United States, 1/2022).  TWA: 2.5 mg/m³ 8 hours. Form: respirable fraction, finescale particles |  |

### **Biological exposure indices**

No exposure indices known.

### **Appropriate engineering** controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Date of issue/Date of revision : 11/9/2023 Date of previous issue Version: 1 4/11 : No previous validation

# Section 8. Exposure controls/personal protection

# Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Skin protection** 

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### **Appearance**

Physical state : Liquid. [Viscous]

Color : Various

Odor : Not available.
Odor threshold : Not available.
pH : 6 to 11

Melting point/freezing point Boiling point, initial boiling point, and boiling range Not available.>100°C (>212°F)

Flash point : Closed cup: >100°C (>212°F) [Pensky-Martens]

Flammability
Lower and upper explosion limit/flammability limit

Not available.Not available.

Vapor pressure :

Date of issue/Date of revision : 11/9/2023 Date of previous issue : No previous validation Version : 1 5/11

# Section 9. Physical and chemical properties and safety characteristics

|  | Vapor Pressure at 20°C |          |        | Vapor pressure at 50°C |     |        |
|--|------------------------|----------|--------|------------------------|-----|--------|
| Ingredient name                                    | mm Hg                  | kPa      | Method | mm Hg                  | kPa | Method |
| butan-2-one O,O',O"-<br>(methylsilylidyne)trioxime | 0.00064                | 0.000085 |        |                        |     |        |

: Not available. **Relative vapor density** : 1.2 to 1.3 **Relative density** 

Solubility(ies)

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

Solubility in water Partition coefficient: n: Not available. : Not applicable.

octanol/water **Auto-ignition temperature** 

**Viscosity** 

: Not available. : Not available. : Not available.

**Particle characteristics** 

**Decomposition temperature** 

Median particle size : Not applicable.

# Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

**Possibility of hazardous** reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Elevated temperature. Incompatible materials.

Incompatible materials : Strong acids, strong alkalis. Strong oxidizing materials.

**Hazardous decomposition** products

: In a fire, decomposition may produce toxic gases/fumes.

# **Section 11. Toxicological information**

### Information on toxicological effects

#### **Acute toxicity**

Not available.

# Irritation/Corrosion

Not available.

### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

### **Carcinogenicity**

Not available.

# Reproductive toxicity

: 11/9/2023 Date of issue/Date of revision 6/11 Date of previous issue : No previous validation Version: 1

# **Section 11. Toxicological information**

Not available.

### **Teratogenicity**

Not available.

# **Specific target organ toxicity (single exposure)**

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation.

**Ingestion** : No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

### Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

### **Numerical measures of toxicity**

**Acute toxicity estimates** 

Date of issue/Date of revision : 11/9/2023 Date of previous issue : No previous validation Version : 1 7/11

# **Section 11. Toxicological information**

| Product/ingredient name              | ( 3     | (mg/kg) | Inhalation<br>(gases)<br>(ppm) | (vapors) | Inhalation<br>(dusts and<br>mists) (mg/ |
|--------------------------------------|---------|---------|--------------------------------|----------|---|
|                                      |         |         |                                |          | I)                                      |
| X-Tenda Coat XTRA Fiber Grade Mastic | 50033.3 | N/A     | N/A                            | N/A      | N/A                                     |

# Section 12. Ecological information

### **Toxicity**

Not available.

### Persistence and degradability

Not available.

# **Bioaccumulative potential**

Not available.

#### **Mobility in soil**

Soil/water partition coefficient (K<sub>oc</sub>)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

# **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

|                               | DOT<br>Classification | TDG<br>Classification | Mexico<br>Classification | IMDG           | IATA           |
|-------------------------------|-----------------------|-----------------------|--------------------------|----------------|----------------|
| UN number                     | Not regulated.        | Not regulated.        | Not regulated.           | Not regulated. | Not regulated. |
| UN proper<br>shipping name    | -                     | -                     | -                        | -              | -              |
| Transport<br>hazard class(es) | -                     | -                     | -                        | -              | -              |
| Packing group                 | -                     | -                     | -                        | -              | -              |
|                               |                       |                       |                          |                |                |

Date of issue/Date of revision : 11/9/2023 Date of previous issue : No previous validation Version : 1 8/11

| X-Tenda Coat XTRA Fiber Grade Mastic |                                   |     |     |     |     |  |  |
|--------------------------------------|-----------------------------------|-----|-----|-----|-----|--|--|
| Section 14                           | Section 14. Transport information |     |     |     |     |  |  |
| Environmental hazards                | No.                               | No. | No. | No. | No. |  |  |

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

# Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs)

: Not listed

**Clean Air Act Section 602** 

: Not listed

**Class I Substances** 

**Clean Air Act Section 602** 

: Not listed

Class II Substances

**DEA List I Chemicals** : Not listed

(Precursor Chemicals)

**DEA List II Chemicals** 

: Not listed

(Essential Chemicals)

**SARA 302/304** 

### **Composition/information on ingredients**

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

Classification : SKIN IRRITATION - Category 2

EYE IRRITATION - Category 2A

### **Composition/information on ingredients**

No products were found.

#### **State regulations**

Massachusetts : The following components are listed: TITANIUM DIOXIDE

**New York** : None of the components are listed.

New Jersey: The following components are listed: TITANIUM DIOXIDEPennsylvania: The following components are listed: TITANIUM OXIDE

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

# International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

### **Montreal Protocol**

Not listed.

# Stockholm Convention on Persistent Organic Pollutants

Not listed.

# **Rotterdam Convention on Prior Informed Consent (PIC)**

Date of issue/Date of revision : 11/9/2023 Date of previous issue : No previous validation Version : 1 9/11

# **Section 15. Regulatory information**

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

### **Inventory list**

Australia : Not determined.

Canada : All components are listed or exempted.China : All components are listed or exempted.

**Eurasian Economic Union**: Russian Federation inventory: All components are listed or exempted.

Japan : Japan inventory (CSCL): Not determined.
Japan inventory (ISHL): Not determined.

New Zealand : All components are listed or exempted.

Philippines : Not determined.

Republic of Korea : Not determined.

Taiwan : All components are listed or exempted.Thailand : All components are listed or exempted.

Turkey: Not determined.

United States : At least one component is not listed.Viet Nam : All components are listed or exempted.

# Section 16. Other information

# **Hazardous Material Information System (U.S.A.)**



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### **National Fire Protection Association (U.S.A.)**



#### Procedure used to derive the classification

| Classification | Justification                   |
|----------------|---------------------------------|
|                | Expert judgment Expert judgment |

#### **History**

Date of printing : 11/9/2023 Date of issue/Date of : 11/9/2023

revision

Date of previous issue : No previous validation

Version : 1

Date of issue/Date of revision : 11/9/2023 Date of previous issue : No previous validation Version : 1 10/11

X-Tenda Coat XTRA Fiber Grade Mastic

# Section 16. Other information

# **Key to abbreviations**

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group

UN = United Nations

#### References

: Not available.

▼ Indicates information that has changed from previously issued version.

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 11/9/2023 Date of previous issue : No previous validation Version : 1 11/11